

TOURING AND CROSSOVER ALL SEASON



CHAMPIRO TOURING A/S



Champiro Touring A/S is an all-season touring tire designed for the latest passenger cars and crossover vehicles. It combines precise handling and control with a quiet and comfortable ride.

Backed by a 60,000 mile limited warranty, the Champiro Touring A/S also delivers great mileage for an outstanding value.



14 - 18 Inch



Speed Rating: T / H / V



50 - 70 Series

UTQG: 540 AA

M + S

Features

Benefits

Four wide circumferential tread grooves

Ensure water drainage and improved wet performance

Full-depth sipes

Improve grip and provide biting edges for all season performance

Large shoulder blocks

Increase tread pattern stiffness for improved handling and cornering

Optimized variable pitch tread blocks

Reduce tread pattern noise for a quieter ride

Rim protector

Helps protect the wheel from curb damage

CHAMPIRO TOURING A/S

TOURING AND CROSSOVER ALL SEASON



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
185/65R14	86H	540 AA	B513	5.5	5.0 - 6.5	1168	530	44	300	10	7.8	23.5	596	7.4	189	17.2	7.8	BSW
195/60R15	88H	540 AA	B510	6.0	5.5 - 7.0	1235	560	44	300	10	7.8	24.2	615	7.9	201	19.1	8.7	BSW
175/65R15	84H	540 AA	B535	5.0	5.0 - 6.0	1102	500	44	300	10	7.8	24.0	609	7.0	177	17.3	7.8	BSW
195/65R15	91H	540 AA	B506	6.0	5.5 - 7.0	1356	615	44	300	10	7.8	25.0	635	7.9	201	19.5	8.8	BSW
205/65R15	94H	540 AA	B529	6.0	5.5 - 7.5	1477	670	44	300	10	7.9	25.5	647	8.2	209	21.9	9.9	BSW
215/70R15	98H	540 AA	B507	6.5	5.5 - 7.0	1653	750	44	300	10	8.0	26.9	683	8.7	221	23.9	10.9	BSW
205/55R16	91H	540 AA	B508	6.5	5.5 - 7.5	1356	615	44	300	10	7.9	24.9	632	8.4	214	20.8	9.4	BSW
215/55R16	93H	540 AA	B530	7.0	6.0 - 7.5	1433	650	44	300	10	8.0	25.3	642	8.9	226	22.8	10.4	BSW
205/60R16	92V	540 AA	B511	6.0	5.5 - 7.5	1389	630	44	300	10	7.9	25.7	652	8.2	209	22.7	10.3	BSW
215/60R16	95H	540 AA	B509	6.5	6.0 - 7.5	1521	690	44	300	10	8.0	26.1	664	8.7	221	23.5	10.6	BSW
215/60R16	95V	540 AA	B528	6.5	6.0 - 7.5	1521	690	44	300	10	8.0	26.1	664	8.7	221	24.2	11.0	BSW
225/60R16	98H	540 AA	B512	6.5	6.0 - 8.0	1653	750	44	300	10	8.1	26.6	676	9.0	228	24.3	11.0	BSW
235/60R16	100H	540 AA	B519	7.0	6.5 - 8.5	1764	800	44	300	10	8.2	27.1	688	9.5	240	27.2	12.3	BSW
205/65R16	95H	540 AA	B595	6.0	5.5 - 7.5	1521	690	44	300	10	7.9	26.5	672	8.2	209	22.8	10.4	BSW
215/65R16	98H	540 AA	B515	6.5	6.0 - 7.5	1653	750	44	300	10	8.0	27.0	686	8.7	221	24.8	11.3	BSW
225/65R16	100T	540 AA	B534	6.5	6.0 - 8.0	1764	800	44	300	10	8.1	27.5	698	9.0	228	25.8	11.7	BSW
235/65R16	103T	540 AA	B526	7.0	6.5 - 8.5	1929	875	44	300	10	8.2	28.0	712	9.5	240	27.5	12.5	BSW
205/50R17	93V XL	540 AA	B596	6.5	5.5 - 7.5	1433	650	50	340	10	7.9	25.1	638	8.4	214	22.3	10.1	BSW
215/50R17	95V XL	540 AA	B597	7.0	6.0 - 7.5	1521	690	50	340	10	8.0	25.5	648	8.9	226	24.3	11.0	BSW
225/50R17	94V	540 AA	B598	7.0	6.0 - 8.0	1477	670	44	300	10	8.1	25.9	658	9.2	233	25.0	11.3	BSW
215/55R17	94V	540 AA	B514	7.0	6.0 - 7.5	1477	670	44	300	10	8.0	26.3	668	8.9	226	25.4	11.5	BSW
225/55R17	97V	540 AA	B518	7.0	6.0 - 8.0	1609	730	44	300	10	8.1	26.8	680	9.2	233	26.0	11.8	BSW
235/55R17	99H	540 AA	B523	7.5	6.5 - 8.5	1709	775	44	300	10	8.2	27.2	690	9.7	245	27.0	12.3	BSW
215/60R17	96H	540 AA	B521	6.5	6.0 - 7.5	1565	710	44	300	10	8.0	27.2	690	8.7	221	24.7	11.2	BSW
225/60R17	99H	540 AA	B520	6.5	6.0 - 8.0	1709	775	44	300	10	8.1	27.6	702	9.0	228	25.8	11.7	BSW
235/60R17	102T	540 AA	B522	7.0	6.5 - 8.5	1874	850	44	300	10	8.2	28.1	714	9.5	240	27.6	12.5	BSW
215/65R17	99T	540 AA	B525	6.5	6.0 - 7.5	1709	775	44	300	10	8.0	28.0	712	8.7	221	25.5	11.6	BSW
225/65R17	102H	540 AA	B517	6.5	6.0 - 8.0	1874	850	44	300	10	8.1	28.5	724	9.0	228	26.4	12.0	BSW
235/65R17	104H	540 AA	B516	7.0	6.5 - 8.5	1984	900	44	300	10	8.1	29.1	738	9.5	240	28.5	12.9	BSW
225/50R18	95T	540 AA	B599	7.0	6.0 - 8.0	1521	690	44	300	10	8.1	26.9	683	9.2	233	25.5	11.6	BSW
235/55R18	100H	540 AA	B537	7.5	6.5 - 8.5	1764	800	44	300	10	8.2	28.2	715	9.7	245	28.2	12.8	BSW
225/60R18	100H	540 AA	B524	6.5	6.0 - 8.0	1764	800	44	300	10	8.1	28.6	727	9.0	228	26.9	12.2	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade BSW Black Side Wall