

# MAXMILER ST

TRAILER SERVICE

13 - 16 Inch 

Speed Rating: M 

75 - 85 Series 

M+S Rated 



Durability



Stability

Maxmiler ST is specifically made for trailer applications. It features sturdy sidewall construction to help reduce trailer sway and enhance load carrying capacity for stable and reliable towing. The robust full width tread design increases contact with the road for better braking performance. Dual steel belts in the tread also enhance handling, stability and puncture resistance.



## FEATURES / BENEFITS

### Full Width Tread

Improved road contact, strong grip and better braking performance

### High Modulus Steel Belts

Enhanced handling, stability and puncture resistance

### Robust Shoulder Blocks

Increased traction and stability

### High-Tech Polyester Casing

Greater durability and reduced trailer sway

### Jointless Nylon Edge Plies

Increased strength and treadwear

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
ST175/80R13	91/87M	C / 6	100A2778	5.0	4.5 - 5.5	1,360/1,200	50	10	24.0	7.0	16.6	BSW
ST205/75R14	100/96M	C / 6	100A2779	5.5	5.0 - 6.0	1,760/1,570	50	10	26.1	8.0	22.5	BSW
ST215/75R14	102/98M	C / 6	100A2781	6.0	5.5 - 7.0	1,870/1,650	50	11	26.7	8.5	24.3	BSW
ST205/75R15	107/102M	D / 8	100A2780	5.5	5.0 - 6.5	2,150/1,870	65	10	27.1	8.0	24.8	BSW
ST225/75R15	117/112M	E / 10	100A2782	6.0	6.0 - 7.0	2,830/2,470	80	11	28.3	8.8	31.4	BSW
ST235/80R16	123/119M	E / 10	100A2783	6.5	6.0 - 7.5	3,420/3,000	80	16	30.8	9.3	40.6	BSW
ST235/85R16	125/121M	E / 10	100A2784	6.5	6.0 - 7.0	3,640/3,200	80	16	31.7	9.3	42.7	BSW

LI Load Index SR Speed Rating (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall

