

INTRODUCING

ICEPRO LT³

STUDDABLE WINTER LIGHT TRUCK

16 - 18 / 20 Inch 

Speed Rating: Q / R 

65 - 80 Series 

M+S Rated 



The new IcePro LT³ is designed for the harshest winter conditions. The rugged tread pattern features dual traction lugs, optimized locking sipes and channel traction edges to ensure the IcePro LT³ has excellent winter performance with or without studs. The icicle sidewall design will look great on your truck or SUV. Whether you are plowing your driveway, going off-road to the jobsite or driving on the highway, the IcePro LT³ will help you get the job done safely this winter.



FEATURES / BENEFITS

Square Shoulder Design

Increased tread depth in the shoulder for better traction and durability

Optimized Locking Sipes

Provides stiffness for cornering yet flexible for winter traction

Staggered Continuous Center Rib

Large biting edges to increase winter grip

Channel Traction Edges

Improves grip in deep snow conditions

Dual Traction Lugs

Grouped lugs in the central zone create more open areas for maximum winter performance

STUDDABLE WINTER LIGHT TRUCK **ICEPROLT³**

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall	Stud Type	Quantity
LT225/75R16	115/112 R	E / 10	100A4231	6.0	6.0 - 7.0	2680/2470	80	16.5	29.3	8.8	34.9	BSW	TSMI 15#	112
LT245/75R16	120/116 R	E / 10	100A4232	7.0	6.5 - 8.0	3042/2778	80	16.5	30.5	9.8	40.2	BSW	TSMI 15#	118
LT245/70R17	119/116 R	E / 10	100A4233	7.0	6.5 - 8.0	3000/2755	80	16.5	30.6	9.8	38.5	BSW	TSMI 15#	118
LT265/70R17	121/118 R	E / 10	100A4234	8.0	7.0 - 8.5	3195/2910	80	16.5	31.7	10.7	42.5	BSW	TSMI 15#	122
LT245/75R17	121/118 R	E / 10	100A4235	7.0	6.5 - 7.5	3195/2910	80	16.5	31.5	9.8	39.5	BSW	TSMI 15#	122
LT235/80R17	120/117 Q	E / 10	100A4236	6.5	6.0 - 7.5	3085/2835	80	16.5	31.8	9.3	38.6	BSW	TSMI 15#	122
LT275/65R18	123/120 R	E / 10	100A4237	8.0	7.5 - 9.0	3415/3085	80	16.5	32.1	11.0	44.2	BSW	TSMI 15#	122
LT265/70R18	124/121 R	E / 10	100A4238	8.0	7.0 - 9.0	3525/3195	80	16.5	32.6	10.7	44.2	BSW	TSMI 15#	126
LT275/70R18	125/122 R	E / 10	100A4239	8.0	7.0 - 8.5	3640/3305	80	16.5	33.2	11.0	46.1	BSW	TSMI 15#	126
LT275/65R20	126/123 R	E / 10	100A4240	8.0	7.5 - 9.5	3750/3415	80	16.5	34.1	11.0	51.1	BSW	TSMI 15#	130

LI Load Index SR Speed Rating XL Extra Load BSW Black Side Wall

