

SAVERO HT2

HIGHWAY ALL-SEASON

30 DAY

Test Drive

15 - 20 Inch 

Speed Rating: R / S / T / H / V 

45 - 85 Series 

UTQG: 520 A B UTQG

M+S Rated **M+S**

50k
Limited
Warranty



Comfort



Noise

Savero HT2 is an all season highway light truck and SUV tire. Active drivers will benefit from the superior pattern design that brings unparalleled handling and control in wet and dry conditions.



FEATURES / BENEFITS

Advanced Tread Design

Excellent handling and ride comfort

Carcass Tension Technology

Ensures balance of dry and wet handling

Noise Canceling Tread

Advanced tread block design effectively reduces road noise

All-Season Compound

Outstanding grip and stability

Tire Size	LI / SR	UTQG	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
P215/70R15	97S	520 A B	B452	6.5	5.5 - 7.0	1,620	44	10	26.9	8.7	24.4	BSW
P235/75R15	105T	520 A B	B443	6.5	6.0 - 8.0	2,028	44	10	28.9	9.3	29.0	OWL
P255/65R16	106S	520 A B	B459	7.5	7.0 - 9.0	2,094	44	10	29.1	10.2	31.8	BSW
P215/70R16	99T	520 A B	B448	6.5	5.5 - 7.0	1,709	44	10	27.9	8.7	25.4	BSW
P225/70R16	101T	520 A B	B462	6.5	6.0 - 7.5	1,819	44	10	28.4	9.0	28.0	OWL
P235/70R16	104T	520 A B	B447	7.0	6.0 - 8.0	1,984	44	10	29.0	9.4	29.4	OWL
P245/70R16	106T	520 A B	B445	7.0	6.5 - 8.0	2,094	44	10	29.5	9.8	31.3	OWL
P255/70R16	109T	520 A B	B433	7.5	6.5 - 8.5	2,271	44	10	30.1	10.2	32.8	OWL
P265/70R16	111T	520 A B	B444	8.0	7.0 - 9.0	2,403	44	10	30.6	10.7	34.9	OWL
P225/75R16	106S XL	520 A B	B549	6.0	6.0 - 7.5	2,094	50	10	29.3	8.8	29.7	OWL
P235/75R16	106T	520 A B	B451	6.5	6.5 - 8.0	2,094	44	10	29.8	9.3	31.6	BSW
P245/75R16	109T	520 A B	B461	7.0	6.5 - 8.0	2,271	44	10	30.5	9.8	33.4	OWL
P265/75R16	114T	520 A B	B436	7.5	7.0 - 9.0	2,601	44	10	31.7	10.5	36.4	OWL
P275/60R17	110T	520 A B	B437	8.0	7.5 - 9.5	2,337	44	10	30.0	11.0	34.8	OWL
225/65R17	102H	520 A B	B538	6.5	6.0 - 8.0	1,874	44	10	28.5	9.0	27.7	BSW
P235/65R17	103T	520 A B	B460	7.0	6.5 - 8.5	1,929	44	10	29.1	9.4	28.7	BSW
P245/65R17	105T	520 A B	B455	7.0	7.0 - 8.5	2,039	44	10	29.5	9.8	30.5	BSW
P255/65R17	108S	520 A B	B454	7.5	7.0 - 9.0	2,205	44	10	30.1	10.2	32.0	BSW
P265/65R17	110T	520 A B	B440	8.0	7.5 - 9.5	2,337	44	10	30.6	10.7	34.9	OWL
P235/70R17	108S XL	520 A B	B438	7.0	6.0 - 8.0	2,205	50	10	30.0	9.4	31.5	OWL
P245/70R17	108T	520 A B	B449	7.0	6.5 - 8.0	2,205	44	10	30.6	9.8	32.6	OWL
P265/70R17	113T	520 A B	B430	8.0	7.0 - 9.0	2,535	44	10	31.7	10.7	35.6	OWL
255/55R18	109V XL	520 A B	B543	8.0	7.0 - 9.0	2,271	50	10	29.0	10.4	34.7	BSW
235/60R18	107V XL	520 A B	B540	7.0	6.5 - 8.5	2,149	50	10	29.1	9.4	30.7	BSW
P245/60R18	104T	520 A B	B442	7.0	7.0 - 8.5	1,984	44	10	29.6	9.8	31.4	BSW
P265/60R18	109T	520 A B	B463	8.0	7.5 - 9.5	2,271	44	10	30.5	10.7	35.1	OWL
P235/65R18	104T	520 A B	B435	7.0	6.5 - 8.5	1,984	44	10	30.0	9.4	31.9	OWL
255/65R18	111T	520 A B										BSW
P265/65R18	112S	520 A B	B548	8.0	7.5 - 9.5	2,469	44	10	31.5	10.7	36.0	OWL
P275/65R18	114T	520 A B	B541	8.0	7.5 - 9.5	2,601	44	10	32.1	11.0	38.1	BSW
P255/70R18	112T	520 A B	B441	7.5	6.5 - 8.5	2,469	44	10	32.1	10.2	35.0	BSW
P265/70R18	114S	520 A B	B545	8.0	7.0 - 9.0	2,601	44	10	32.6	10.7	38.2	OWL
P245/55R19	103S	520 A B	B542	7.5	7.0 - 8.5	1,929	44	10	29.6	10.0	33.0	BSW
P255/60R19	108H	520 A B										BSW
275/45R20	110V XL	520 A B	B550	9.0	8.5 - 10.5	2,337	50	10	29.8	10.7	35.4	BSW
255/50R20	105H	520 A B	B621	8.0	7.0 - 9.0	2,039	44	10	30.1	10.4	35.0	BSW
265/50R20	107V	520 A B										BSW
P255/55R20	107H	520 A B										BSW
P275/55R20	111H	520 A B	B539	8.5	7.5 - 9.5	2,403	44	10	31.9	11.2	39.3	BSW
P275/60R20	114S	520 A B	B432	8.0	7.5 - 9.5	2,601	44	10	33.0	11.0	39.0	OWL

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
30X9.50R15LT	104R	C / 6	B458	7.5	6.5 - 8.5	1,985	50	13	29.5	9.4	35.9	OWL
31X10.50R15LT	109R	C / 6	B446	8.5	7.0 - 9.0	2,270	50	13	30.5	10.6	40.8	OWL
LT235/75R15	104/101R	C / 6	B453	6.5	6.0 - 7.0	1,985/1,820	50	13	28.9	9.3	35.7	OWL
LT225/75R16	115/112R	E / 10	B457	6.0	6.0 - 7.0	2,680/2,470	80	13	29.3	8.8	37.4	BSW
LT245/75R16	120/116S	E / 10	B456	7.0	6.5 - 8.0	3,042/2,778	80	13	30.5	9.8	42.7	OWL
LT265/75R16	123/120R	E / 10	B434	7.5	7.0 - 8.0	3,415/3,085	80	13	31.7	10.5	47.5	OWL
LT215/85R16	115/112R	E / 10	B544	6.0	5.5 - 7.0	2,680/2,470	80	13	30.4	8.5	38.5	BSW
LT235/85R16	120/116R	E / 10	B450	6.5	6.0 - 7.5	3,042/2,778	80	13	31.7	9.3	42.9	BSW
LT245/70R17	119/116R	E / 10	B439	7.0	6.5 - 8.0	3,000/2,755	80	13	30.6	9.8	41.4	BSW
LT265/70R17	121/118R	E / 10	B431	8.0	7.0 - 8.5	3,195/2,910	80	13	31.7	10.7	46.9	OWL
LT245/75R17	121/118S	E / 10	B547	7.0	6.5 - 7.5	3,195/2,910	80	13	31.5	9.8	44.4	BSW
LT235/80R17	120/117R	E / 10	B546	6.5	6.0 - 7.5	3,085/2,835	80	13	31.8	9.3	42.8	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall OWL Outline White Letter **COMING IN 2021**