

ADVENTURO HT

HIGHWAY ALL-SEASON

30 DAY

Test Drive

15 - 20 Inch 

Speed Rating: R/S/T/H/V 

50 - 85 Series 

UTQG: 600 A B UTQG

M+S Rated M+S

60K
50k

Limited Warranty
(60k for LT Sizes)



Handling



Comfort



Noise

Adventuro HT is designed with comfort and control in mind. The advanced tread design and robust 60,000 mile tread life warranty offer drivers the optimal balance of form and function. With features like full depth sipes, chamfered tread edges and a continuous center rib, you can drive with confidence and control. Dual sidewall designs also give you the ability to choose the perfect look for your vehicle.



FEATURES / BENEFITS

Full Depth Wave Sipes

Additional biting edges for improved wet and snow traction

Chamfered Tread Edges

Increased displacement of water to reduce the risk of hydroplaning

Dual Sidewall Design

Two choices for the perfect look

Continuous Center Rib

Improved braking performance and excellent stability at highway speeds

Harmonically Optimized Pitch Sequencing

Reduced road noise generation for a quieter ride

HIGHWAY ALL-SEASON **ADVENTURO HT**

Tire Size	LI / SR	UTQG	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
P235/75R15	105T	600 A B	100UA3630	6.5	6.0 - 8.0	2,028	44	11	29.0	9.5	27.5	BSW
P215/70R16	99T	600 A B	100UA3606	6.5	5.5 - 7.0	1,709	44	11	28.0	8.8	23.9	BSW
P235/70R16	104T	600 A B	100UA3622	7.0	6.0 - 8.0	1,984	44	11	29.1	9.5	27.9	BSW
P245/70R16	106T	600 A B	100UA3628	7.0	6.5 - 8.0	2,094	44	11	29.6	9.9	29.4	BSW
P255/70R16	109T	600 A B	100UA3627	7.5	6.5 - 8.5	2,271	44	11	30.2	10.2	30.4	BSW
P265/70R16	111T	600 A B	100UA3624	8.0	7.0 - 9.0	2,403	44	11	30.7	10.7	32.5	BSW
P245/75R16	109T	600 A B	100UA3626	7.0	6.5 - 8.0	2,271	44	11	30.6	9.9	31.2	BSW
P265/75R16	114T	600 A B	100UA3632	7.5	7.0 - 9.0	2,601	44	11	31.7	10.6	33.2	BSW
P245/65R17	105T	600 A B	100UA3623	7.0	7.0 - 8.5	2,039	44	11	29.7	9.7	28.7	BSW
P265/65R17	110T	600 A B	AS124	8.0	7.5 - 9.5	2,337	44	11	30.6	10.7	34.9	OWL
P245/70R17	108T	600 A B	100UA3625	7.0	6.5 - 8.0	2,205	44	11	30.7	9.8	31.1	BSW
P265/70R17	113T	600 A B	100UA3621	8.0	7.0 - 9.0	2,535	44	11	31.7	10.8	34.2	BSW
255/55R18	109V XL	600 A B	AS125	8.0	7.0 - 9.0	2,271	50	11	29.0	10.4	34.0	BSW
P265/60R18	109T	600 A B	AS126	8.0	7.5 - 9.5	2,271	44	11	30.5	10.7	35.0	BSW
P265/65R18	112T	600 A B	AS127	8.0	7.5 - 9.5	2,469	44	11	31.5	10.7	35.8	OWL
P275/65R18	114T	600 A B	AS128	8.0	7.5 - 9.5	2,601	44	11	32.1	11.0	38.0	BSW
P255/70R18	112T	600 A B	AS129	7.5	6.5 - 8.5	2,469	44	11	32.1	10.2	35.0	BSW
P265/70R18	114T	600 A B	AS130	8.0	7.0 - 9.0	2,601	44	11	32.6	10.7	38.2	OWL
P245/55R19	103T	600 A B	AS131	7.5	7.0 - 8.5	1,929	44	11	29.7	10.0	33.0	BSW
P255/60R19	108H	600 A B	AS132	7.5	7.0 - 9.0	2,205	44	11	31.1	10.2	34.6	BSW
255/50R20	105H	600 A B	AS133	8.0	7.0 - 9.0	2,039	44	11	30.1	10.4	34.4	BSW
265/50R20	107T	600 A B	AS134	8.5	7.5 - 9.5	2,150	44	11	30.5	10.9	36.4	BSW
P255/55R20	107H	600 A B	AS135	8.0	7.0 - 9.0	2,149	44	11	31.0	10.4	36.6	BSW
P275/55R20	111H	600 A B	100UA3601	8.5	7.5 - 9.5	2,403	44	11	31.9	11.2	36.5	BSW
P275/60R20	114H	600 A B	AS136	8.0	7.5 - 9.5	2,601	44	11	33.0	11.0	39.2	BSW

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
LT225/75R16	115/112S	E / 10	AS137	6.0	6.0 - 7.0	2,680/2,470	80	13	29.3	8.8	37.3	BSW
LT245/75R16	120/116S	E / 10	AS138	7.0	6.5 - 8.0	3,042/2,778	80	13	30.5	9.8	41.8	BSW
LT265/75R16	123/120S	E / 10	AS139	7.5	7.0 - 8.0	3,415/3,085	80	13	31.7	10.5	47.5	OWL
LT235/85R16	120/116S	E / 10	AS140	6.5	6.0 - 7.5	3,042/2,778	80	13	31.7	9.3	42.9	BSW
LT265/70R17	121/118S	E / 10	AS141	8.0	7.0 - 8.5	3,195/2,910	80	13	31.7	10.7	47.6	OWL
LT245/75R17	121/118S	E / 10	AS142	7.0	6.5 - 7.5	3,195/2,910	80	13	31.5	9.8	44.4	BSW
LT235/80R17	120/117R	E / 10	AS143	6.5	6.0 - 7.5	3,085/2,835	80	13	31.8	9.3	42.8	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall OWL Outline White Letter

