

MAXMILER Pro

COMMERCIAL VAN ALL-SEASON

15 - 17 Inch 

Speed Rating: Q / R / T / H 

55 - 65 / 75 - 85 Series 

UTQG: 700 A A UTQG

M+S Rated **M+S**



Noise



Durability



Stability

Maxmiler Pro is designed for today's light commercial vehicles like Ford Transit, Nissan NV and RAM ProMaster. The durable reinforced sidewall is built to carry the heavy loads of compact and full-size multi-purpose vans. The tread pattern delivers all-season performance for highway use with the toughness needed for some off-road driving near the jobsite. Maxmiler Pro—your partner in business to get the job done.



FEATURES / BENEFITS

Square Footprint

Even pressure distribution which resists irregular wear and improves tire mileage

Large Siped Shoulder Blocks

Improved stability, braking and wet/dry grip

Wide Tread Grooves

Enhanced water evacuation for excellent hydroplaning resistance

Reinforced Sidewall

Heavy load carrying capacity for commercial multi-purpose vans

Low Rolling Resistance

Reduced fuel consumption

COMMERCIAL VAN ALL-SEASON **MAXMILER Pro**

Tire Size	LI / SR	UTQG	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
P205/65R15	95T XL	700 A A	B624	6.0	5.5 - 7.5	1,521	50	11	25.5	8.2	24.0	BSW
215/55R16	97H XL	700 A A	B625	7.0	6.0 - 7.5	1,609	50	11	25.3	8.9	24.3	BSW

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
185/60R15C	94/92T	-	B623	5.5	5.5 - 6.0	1,475/1,390	55	12	23.7	7.4	21.4	BSW
235/65R16C	121/119R	-	B626	7.0	6.5 - 7.5	3,195/3,000	85	13	28.0	9.4	38.1	BSW
225/75R16C	121/120R	-	B627	6.0	6.0 - 7.0	3,195/3,085	85	13	29.3	8.8	38.1	BSW
LT245/75R16	120/116Q E	E / 10	B631	7.0	6.5 - 8.0	3,042/2,778	80	14	30.5	9.8	44.3	BSW
LT215/85R16	115/112Q E	E / 10	B628	6.0	5.5 - 7.0	2,680/2,470	80	13	30.4	8.7	39.9	BSW
LT235/85R16	120/116R E	E / 10	B630	6.5	6.0 - 7.5	3,042/2,778	80	13	31.7	9.3	45.0	BSW
LT245/75R17	121/118R E	E / 10	B632	7.0	6.5 - 7.5	3,195/2,910	80	14	31.5	9.8	46.3	BSW
LT235/80R17	120/117R E	E / 10	B629	6.5	6.0 - 7.5	3,085/2,835	80	13	31.8	9.3	44.8	BSW

LI Load Index **SR** Speed Rating **XL** Extra Load **UTQG** Uniform Tire Quality Grade **(s/d)** Single/Dual **LR** Load Range **PR** Ply Rating **BSW** Black Side Wall