

ADVENTURO AT³

ON / OFF ROAD ALL-TERRAIN

30 DAY

Test Drive

15 / 16 / 17 / 18 / 20 Inch 

Speed Rating: R / S / T / H 

55 - 85 Series 

UTQG: 520 A B 

M+S Rated 

50k

Limited Warranty
(P-Metric Only)



Handling



Comfort



On / Off Road

Adventuro AT³ is an all-terrain tire for pickup and SUV drivers wanting aggressive looks and civilized on-road manners. The enhanced tread compound and dual-purpose tread design provides excellent handling, wet grip and a comfortable ride and is backed by a 50,000 mile tread life warranty. Superb off-road capabilities are maintained with features that provide stability and grip on soft and loose surfaces as well as a self-cleaning tread design.

FEATURES / BENEFITS

Dual-Purpose Tread Design

Balanced on-road and off-road performance

Interlocked Center Rib

Superior handling, stability and grip on both soft and loose surfaces

Five-Pitch Technology

Reduced tire noise

3D Chamfered-Edge Grooves

Self-cleaning tread design for off-road performance

Enhanced Compound

Provides wet and dry grip, longer tread life and improved cut/chip resistance



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
P235/75R15	105S	520 A B	AS087	6.5	6.0 - 8.0	2,028	44	13	28.9	9.3	30.2	OWL
P235/70R16	104T	520 A B	AS081	7.0	6.0 - 8.0	1,984	44	13	29.0	9.5	30.9	OWL
P265/70R16	111T	520 A B	AS079	8.0	7.0 - 9.0	2,403	44	13	30.6	10.7	34.8	OWL
P245/75R16	109T	520 A B	AS083	7.0	6.0 - 8.0	2,271	44	13	30.5	9.8	33.9	OWL
P245/65R17	105T	520 A B	AS082	7.0	7.0 - 8.5	2,039	44	13	29.5	9.8	31.8	OWL
P265/65R17	110T	520 A B	AS085	8.0	7.5 - 9.5	2,337	44	13	30.6	10.7	34.4	OWL
P245/70R17	108T	520 A B	AS084	7.0	6.5 - 8.0	2,205	44	13	30.6	9.8	33.7	OWL
P265/70R17	113T	520 A B	AS077	8.0	7.0 - 9.0	2,535	44	13	31.7	10.7	36.9	OWL
P285/70R17	117T	520 A B	AS091	8.5	7.5 - 9.5	2,833	44	13	32.8	11.5	42.4	OWL
P235/75R17	108S	520 A B	AS089	6.5	6.0 - 8.0	2,205	44	13	30.9	9.3	33.2	OWL
P265/60R18	109T	520 A B	AS088	8.0	7.5 - 9.5	2,271	44	13	30.5	10.7	35.8	OWL
P265/65R18	112S	520 A B	AS086	8.0	7.5 - 9.5	2,469	44	13	31.5	10.7	36.3	OWL
P275/65R18	114T	520 A B	AS078	8.0	7.5 - 9.5	2,601	44	13	32.1	11.0	39.2	OWL
P265/70R18	114S	520 A B	AS090	8.0	7.0 - 9.0	2,601	44	13	32.6	10.7	38.3	OWL
P275/55R20	111H	520 A B	AS080	8.5	7.5 - 9.5	2,403	44	13	31.9	11.2	39.8	BSW

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
31X10.50R15LT	109S	C / 6	AS093	8.5	7.0 - 9.0	2,270	50	16	30.5	10.6	40.9	OWL
LT245/75R16	120/116S	E / 10	AS101	7.0	6.5 - 8.0	3,042/2,778	80	16	30.5	9.8	42.7	OWL
LT265/75R16	123/120S	E / 10	AS092	7.5	7.0 - 8.0	3,415/3,085	80	16	31.7	10.5	48.5	OWL
LT285/75R16	126/123R	E / 10	AS094	8.0	7.5 - 9.0	3,750/3,415	80	16	32.8	11.3	51.4	OWL
LT215/85R16	115/112S	E / 10	AS104	6.0	5.5 - 7.0	2,680/2,470	80	16	30.4	8.5	39.8	OWL
LT235/85R16	120/116S	E / 10	AS099	6.5	6.0 - 7.5	3,042/2,778	80	16	31.7	9.3	44.9	BSW
LT245/70R17	119/116S	E / 10	AS103	7.0	6.5 - 8.0	3,000/2,755	80	16	30.6	9.8	44.0	OWL
LT265/70R17	121/118S	E / 10	AS102	8.0	7.0 - 8.5	3,195/2,910	80	16	31.7	10.7	48.1	OWL
LT285/70R17	121/118S	E / 10	AS095	8.5	7.5 - 9.0	3,195/2,910	80	16	32.8	11.5	52.8	OWL
LT245/75R17	121/118S	E / 10	AS097	7.0	6.5 - 7.5	3,195/2,910	80	16	31.5	9.8	46.1	OWL
LT235/80R17	120/117S	E / 10	AS100	6.5	6.0 - 7.5	3,085/2,835	80	16	31.8	9.3	44.0	OWL
LT275/65R18	123/120S	E / 10	AS098	8.0	7.5 - 9.0	3,415/3,085	80	16	32.1	11.0	49.9	OWL
LT285/65R18	125/122S	E / 10	AS105	8.5	8.0 - 10.0	3,640/3,305	80	16	32.6	11.5	51.4	OWL
LT275/70R18	125/122S	E / 10	AS096	8.0	7.0 - 8.5	3,640/3,305	80	16	33.2	11.0	52.0	OWL

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall OWL Outline White Letter