

# INTRODUCING

# ADVENTURO ATZ

ON / OFF ROAD ALL-TERRAIN

30 DAY

Test Drive

15 - 18 / 20 , 22 Inch 

Speed Rating: R / S / T / H 

45 - 80 Series 

UTQG: 600 A B 

M+S Rated 

60K  
55k

Limited Warranty  
(95k for LT & Fleet Sizes)



3PMS



Handling



Comfort



On / Off Road



Road Hazard  
Warranty



24HR  
Roadside  
Assistance

The GT Radial Adventuro ATZ is built for all-season adventure, combining rugged off-road capability with on-road comfort. Its Three-Peak Mountain Snowflake (3PMS) rating delivers confident traction in severe snow, while interconnected tread blocks with microgrooves enhance stability and wet grip. Staggered shoulder blocks provide enhanced traction on tough terrain, and reinforced sidewalls add durability, protection, and aggressive style for wherever the road—or trail—leads.

## FEATURES / BENEFITS

**Interconnected Center Tread Blocks with Multi-Microgrooves**  
Improves on-road stability and handling with increased grip in wet conditions

**Three-Peak Mountain Snowflake (3PMS) Rating**  
Improved snow traction over a standard all-season rated tire

**Staggered Shoulder Blocks**  
Enhanced traction in thick terrain and challenging off-road surfaces

**Reinforced Two-Sided Sidewall Construction**  
Combining aggressive styling with additional sidewall protection and biting edges when encountering rough terrain

DUAL SIDEWALL DESIGN



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
235/75R15	109T XL	600 A B	100UA3200	6.5	6.0 - 8.0	2,271	50	13.5	29.1	9.3	35.2	BSW
265/70R16	112T	600 A B	100UA3202	8.0	7.0 - 9.0	2,469	44	13.5	30.9	10.7	42.3	BSW
245/75R16	111T	600 A B	100UA3201	7.0	6.5 - 8.0	2,403	44	13.5	30.7	9.8	41.0	BSW
265/75R16	116T	600 A B	100UA3226	7.5	7.0 - 9.0	2,756	44	13.5	31.9	10.5	43.9	BSW
225/65R17	102H	600 A B	100UA3213	6.5	6.0 - 8.0	1,874	44	13.5	28.7	9.0	34.0	BSW
235/65R17	104H	600 A B	100UA3280	7.0	6.5 - 8.5	1,984	44	13.5	29.3	9.5	36.2	BSW
245/65R17	111T XL	600 A B	100UA3204	7.0	7.0 - 8.5	2,403	50	13.5	29.8	9.8	37.7	BSW
265/65R17	112T	600 A B	100UA3205	8.0	7.5 - 9.5	2,469	44	13.5	30.8	10.7	42.1	BSW
255/70R17	112T	600 A B	100UA3215	7.5	6.5 - 8.5	2,469	44	13.5	31.3	10.2	41.4	BSW
265/70R17	115T	600 A B	100UA3206	8.0	7.0 - 9.0	2,679	44	13.5	31.7	10.6	41.0	BSW
285/70R17	117T	600 A B	100UA3217	8.5	7.5 - 9.5	2,833	44	13.5	33.0	11.5	47.6	BSW
245/60R18	105H	600 A B	100UA3281	7.0	7.0 - 8.5	2,039	44	13.5	29.8	9.8	37.3	BSW
265/60R18	110T	600 A B	100UA3207	8.0	7.5 - 9.5	2,337	44	13.5	30.8	10.7	41.7	BSW
265/65R18	114T	600 A B	100UA3208	8.0	7.5 - 9.5	2,601	44	13.5	31.8	10.7	43.7	BSW
275/65R18	116T	600 A B	100UA3210	8.0	7.5 - 9.5	2,756	44	13.5	32.0	11.0	43.2	BSW
255/70R18	113T	600 A B	100UA3218	7.5	6.5 - 8.5	2,535	44	13.5	32.3	10.2	42.5	BSW
265/50R20	111T XL	600 A B	100UA3219	8.5	7.5 - 9.5	2,403	50	13.5	30.7	10.9	40.1	BSW
275/55R20	117H XL	600 A B	100UA3211	8.5	7.5 - 9.5	2,833	50	13.5	32.0	11.5	43.7	BSW
275/60R20	115H	600 A B	100UA3227	8.0	7.5 - 9.5	2,679	44	13.5	32.9	11.0	44.5	BSW
285/45R22	114H XL	600 A B	100UA3220	9.5	9.0 - 10.5	2,601	50	13.5	32.1	11.2	42.3	BSW

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
35X12.50R18LT	128R	F/12	100UA3262	10.0	8.5 - 11.0	3,970	80	18.5	34.8	12.5	69.2	BSW
35X12.50R20LT	125R	F/12	100UA3264	10.0	8.5 - 11.0	3,460	80	18.5	34.6	12	62.4	BSW
LT225/75R16	115/112S	E/10	100UA3252	6.0	6.0 - 7.5	2,680 / 2,470	80	16.0	29.5	8.8	43.2	BSW
LT245/75R16	120/116S	E/10	100UA3231	7.0	6.5 - 8.0	3,042 / 2,778	80	16.0	30.7	9.8	48.9	BSW
LT265/75R16	123/120S	E/10	100UA3232	7.5	7.0 - 9.0	3,415 / 3,085	80	16.0	31.9	10.5	54.2	BSW
LT285/75R16	126/123R	E/10	100UA3253	8.0	7.5 - 9.5	3,750 / 3,415	80	16.0	33.1	11.3	59.5	BSW
LT245/70R17	119/116S	E/10	100UA3234	7.0	6.5 - 8.0	3,000 / 2,755	80	16.0	30.8	9.8	48.1	BSW
LT265/70R17	123/120S	E/10	100UA3236	8.0	7.0 - 9.0	3,415 / 3,085	80	16.0	31.7	10.2	48.3	BSW
LT285/70R17	126/123S	E/10	100UA3237	8.5	7.5 - 9.5	3,750 / 3,415	80	16.0	32.8	11.0	52.9	BSW
LT245/75R17	121/118S	E/10	100UA3235	7.0	6.5 - 8.0	3,195 / 2,910	80	16.0	31.5	9.4	46.3	BSW
LT235/80R17	120/117R	E/10	100UA3233	6.5	6.0 - 8.0	3,085 / 2,835	80	16.0	32.1	9.3	48.7	BSW
LT275/65R18	123/120S	E/10	100UA3241	8.0	8.0 - 9.5	3,415 / 3,085	80	16.0	32.1	10.6	51.6	BSW
LT265/70R18	124/121S	E/10	100UA3240	8.0	7.0 - 9.0	3,525 / 3,195	80	16.0	32.9	10.7	55.6	BSW
LT275/70R18	125/122S	E/10	100UA3242	8.0	7.0 - 9.0	3,640 / 3,305	80	16.0	33.2	10.5	47.0	BSW
LT275/55R20	120/117T	E/10	100UA3245	8.5	8.0 - 9.5	3,085 / 2,835	80	16.0	32.1	11.2	54.0	BSW
LT265/60R20	121/118S	E/10	100UA3244	8.0	8.0 - 9.5	3,195 / 2,910	80	16.0	32.5	10.7	54.7	BSW
LT275/60R20	123/120S	E/10	100UA3246	8.0	8.0 - 9.5	3,415 / 3,085	80	16.0	33.2	11.0	56.0	BSW
LT285/60R20	125/122S	E/10	100UA3248	8.5	8.5 - 10.0	3,640 / 3,305	80	16.0	33.7	11.5	59.7	BSW
LT275/65R20	126/123S	E/10	100UA3247	8.0	8.0 - 9.5	3,750 / 3,415	80	16.0	34.2	10.8	56.2	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall OWL Outline White Letter

