

# INTRODUCING

# ADVENTURO RT

ON / OFF ROAD RUGGED TERRAIN

30 DAY

Test Drive

16 - 18 / 20 , 22 Inch 

Speed Rating: R / S / T / H 

45 - 80 Series 

UTQG: 500 A B 

M+S Rated 

50K  
45K

Limited Warranty  
(45K for LT & Fleet Sizes)



Handling



Comfort



On / Off Road



Road Hazard  
Warranty

24HR

Roadside  
Assistance

Conquer every trail and command the road with the new GT Radial Adventuro RT. It features an aggressive dual sidewall design for style, traction, and added protection. Wide-groove, staggered shoulder lugs claw through mud and dirt for reliable performance, while stone rejectors help guard against belt damage. An interconnected center lug pattern improves driver feel and responsiveness. Built tough for any terrain, the Adventuro RT is ready for the ultimate off-road challenge.

## FEATURES / BENEFITS

### Stone Rejectors

Reduces belt damage by minimizing stone and gravel retention

### Wide Groove Staggered Shoulder Lugs

Enhanced off-road traction and bite with increased mud and dirt evacuation

### Aggressive Dual Sidewall Design

Two unique sidewall designs to fit the consumer and vehicle personality, while providing added performance in deep soil, on loose or rough terrain, and additional upper sidewall protection

### Interconnected Center Lug Pattern

Improves driver feel and responsiveness

DUAL SIDEWALL DESIGN



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
265/70R17	115T	500 A B	100UA3806	8.0	7.0 - 9.0	2,679	44	13.5	31.7	10.6	41.0	BSW
265/65R18	114T	500 A B	100UA3808	8.0	7.5 - 9.5	2,601	44	13.5	31.8	10.7	43.7	BSW
275/65R18	116T	500 A B	100UA3810	8.0	7.5 - 9.5	2,756	44	13.5	32.0	11.0	43.2	BSW
275/55R20	117H XL	500 A B	100UA3811	8.5	7.5 - 9.5	2,833	50	13.5	32.0	11.5	43.7	BSW
275/60R20	115H	500 A B	100UA3827	8.0	7.5 - 9.5	2,679	44	13.5	32.9	11.0	44.5	BSW
285/45R22	114H XL	500 A B	100UA3820	9.5	9.0 - 10.5	2,601	50	13.5	32.1	11.2	42.3	BSW

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
35X12.50R17LT	125R	E/10	100UA3860	10.0	8.0 - 10.5	3,640	65	18.5	34.8	12.5	70.1	BSW
33X12.50R18LT	122R	F/12	100UA3861	10.0	8.5 - 11.0	3,305	80	18.5	32.8	12.5	63.9	BSW
35X12.50R18LT	128R	F/12	100UA3862	10.0	8.5 - 11.0	3,970	80	18.5	34.8	12.5	69.2	BSW
33X12.50R20LT	119R	F/12	100UA3863	10.0	8.5 - 11.0	3,000	80	18.5	32.8	12.5	62.2	BSW
35X12.50R20LT	125R	F/12	100UA3864	10.0	8.5 - 11.0	3,640	80	18.5	34.6	12.0	62.4	BSW
35X12.50R22LT	121R	F/12	100UA3866	10.0	8.5 - 11.0	3,195	80	18.5	34.8	12.5	65.3	BSW
LT245/75R16	120/116S	E/10	100UA3831	7.0	6.5 - 8.0	3,042 / 2,778	80	16.0	30.7	9.8	48.9	BSW
LT265/75R16	123/120S	E/10	100UA3832	7.5	7.0 - 9.0	3,415 / 3,085	80	16.0	31.9	10.5	54.2	BSW
LT245/70R17	119/116S	E/10	100UA3834	7.0	6.5 - 8.0	3,000 / 2,755	80	16.0	30.8	9.8	48.1	BSW
LT265/70R17	123/120S	E/10	100UA3836	8.0	7.0 - 9.0	3,415 / 3,085	80	16.0	31.2	10.2	48.3	BSW
LT285/70R17	126/123S	E/10	100UA3837	8.5	7.5 - 9.5	3,750 / 3,415	80	16.0	32.8	11.0	59.5	BSW
LT315/70R17	126/123S	E/10	100UA3838	9.5	8.0 - 10.5	3,750 / 3,415	80	16.0	34.7	12.7	68.1	BSW
LT245/75R17	121/118S	E/10	100UA3835	7.0	6.5 - 8.0	3,195 / 2,910	80	16.0	31.5	9.4	46.3	BSW
LT235/80R17	120/117R	E/10	100UA3833	6.5	6.0 - 8.0	3,085 / 2,835	80	16.0	32.1	9.3	48.7	BSW
LT275/65R18	123/120S	E/10	100UA3841	8.0	8.0 - 9.5	3,415 / 3,085	80	16.0	32.1	10.6	51.6	BSW
LT285/65R18	125/122S	E/10	100UA3843	8.5	8.5 - 10.0	3,640 / 3,305	80	16.0	32.8	11.5	58.6	BSW
LT265/70R18	124/121S	E/10	100UA3840	8.0	7.0 - 9.0	3,525 / 3,195	80	16.0	32.9	10.7	55.6	BSW
LT275/70R18	125/122S	E/10	100UA3842	8.0	7.0 - 9.0	3,640 / 3,305	80	16.0	33.2	10.5	47.0	BSW
LT295/70R18	129/126R	E/10	100UA3867	8.5	7.5 - 10.0	4,080 / 3,750	80	16.0	34.5	11.8	64.4	BSW
LT275/55R20	120/117T	E/10	100UA3845	8.5	8.0 - 9.5	3,085 / 2,835	80	16.0	32.1	11.2	54.0	BSW
LT265/60R20	121/118S	E/10	100UA3844	8.0	8.0 - 9.5	3,195 / 2,910	80	16.0	32.5	10.7	54.7	BSW
LT275/60R20	123/120S	E/10	100UA3846	8.0	8.0 - 9.5	3,415 / 3,085	80	16.0	33.2	11.0	56.0	BSW
LT285/60R20	125/122S	E/10	100UA3848	8.5	8.5 - 10.0	3,640 / 3,305	80	16.0	33.7	11.5	59.7	BSW
LT295/60R20	126/123S	E/10	100UA3849	8.5	8.5 - 10.5	3,750 / 3,415	80	16.0	34.2	11.8	68.8	BSW
LT275/65R20	126/123S	E/10	100UA3847	8.0	8.0 - 9.5	3,750 / 3,415	80	16.0	34.2	10.8	56.2	BSW
LT295/65R20	129/126S	E/10	100UA3850	8.5	8.5 - 10.5	4,080 / 3,750	80	16.0	35.4	11.8	72.3	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall OWL Outline White Letter

