

# HIGHWAY ALL SEASON

## SAVERO HT2

SATISFACTION  
**30** DAY  
TEST DRIVE  
GUARANTEE



<b>50</b> 50,000 Mile Limited Warranty <small>25,000 miles for rear of split firm</small>	Highway Terrain	Symmetrical	Handling	Water Evacuation	All Season	<b>5</b> 5 Year Limited Warranty
--	-----------------	-------------	----------	------------------	------------	--

Savero HT2 is an all season highway light truck and SUV tire. Active drivers will benefit from the

superior pattern design that brings unparalleled handling and control in wet and dry conditions.

15 - 20 inch

Speed Rating: R / S / T / H / V

45 / 55 - 85 Series

UTQG: 520 A B

M + S

### Features

### Benefits

Superior tread pattern design

Offers excellent handling and ride comfort

Advanced tread compound

Provides outstanding grip and stability

Optimized carcass tension technology

Ensures balance of dry and wet handling

Advanced noise cancelling technology in tread block design

Effectively reduces road noise

# SAVERO HT2

## HIGHWAY ALL SEASON



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 <sup>nd</sup>	mm	inch	mm	inch	mm	lbs	kg	
P215/70R15	97S	520 A B	B452	6.5	5.5 - 7.0	1620	735	44	300	10	8.2	26.9	683	8.7	221	23.8	10.8	BSW
P235/75R15	105T	520 A B	B443	6.5	6.0 - 8.0	2028	920	44	300	10	8.2	28.9	733	9.3	235	29.8	13.5	OWL
P255/65R16	106S	520 A B	B459	7.5	7.0 - 9.0	2094	950	44	300	10	8.2	29.1	738	10.2	260	30.0	13.6	BSW
P215/70R16	99T	520 A B	B448	6.5	5.5 - 7.0	1709	775	44	300	10	8.2	27.9	708	8.7	221	24.9	11.3	BSW
P225/70R16	101T	520 A B	B462	6.5	6.0 - 7.5	1819	825	44	300	10	8.2	28.4	722	9.0	228	27.3	12.4	OWL
P235/70R16	104T	520 A B	B447	7.0	6.0 - 8.0	1984	900	44	300	10	8.2	29.0	736	9.4	240	30.0	13.6	OWL
P245/70R16	106T	520 A B	B445	7.0	6.5 - 8.0	2094	950	44	300	10	8.2	29.5	750	9.8	248	31.3	14.2	OWL
P255/70R16	109T	520 A B	B433	7.5	6.5 - 8.5	2271	1030	44	300	10	8.2	30.1	764	10.2	260	33.1	15.0	OWL
P265/70R16	111T	520 A B	B444	8.0	7.0 - 9.0	2403	1090	44	300	10	8.2	30.6	778	10.7	272	34.7	15.8	OWL
P225/75R16	106S XL	520 A B	B549	6.0	6.0 - 7.5	2094	950	50	340	10	8.2	29.3	744	8.8	233	28.3	12.8	OWL
P235/75R16	106T	520 A B	B451	6.5	6.5 - 8.0	2094	950	44	300	10	8.2	29.8	758	9.3	235	30.8	14.0	BSW
P245/75R16	109T	520 A B	B461	7.0	6.5 - 8.0	2271	1030	44	300	10	8.2	30.5	774	9.8	248	34.0	15.4	OWL
P265/75R16	114T	520 A B	B436	7.5	7.0 - 9.0	2601	1180	44	300	10	8.2	31.7	804	10.5	267	35.4	16.1	OWL
P275/70R17	110T	520 A B	B437	8.0	7.5 - 9.5	2337	1060	44	300	10	8.2	30.0	762	11.0	279	35.0	15.9	OWL
225/65R17	102H	520 A B	B538	6.5	6.0 - 8.0	1874	850	44	300	10	8.2	28.5	724	9.0	228	25.3	11.5	BSW
P235/65R17	103T	520 A B	B460	7.0	6.5 - 8.5	1929	875	44	300	10	8.2	29.1	738	9.4	240	27.6	12.5	BSW
P245/65R17	105T	520 A B	B455	7.0	7.0 - 8.5	2039	925	44	300	10	8.2	29.5	750	9.8	248	30.3	13.8	BSW
P255/65R17	108S	520 A B	B454	7.5	7.0 - 9.0	2205	1000	44	300	10	8.2	30.1	764	10.2	260	31.4	14.2	BSW
P265/65R17	110T	520 A B	B440	8.0	7.5 - 9.5	2337	1060	44	300	10	8.2	30.6	776	10.7	272	34.4	15.6	OWL
P235/70R17	108S XL	520 A B	B438	7.0	6.0 - 8.0	2205	1000	50	340	10	8.2	30.0	762	9.4	240	30.3	13.7	OWL
P245/70R17	108T	520 A B	B449	7.0	6.5 - 8.0	2205	1000	44	300	10	8.2	30.6	776	9.8	248	33.2	15.1	OWL
P265/70R17	113T	520 A B	B430	8.0	7.0 - 9.0	2535	1150	44	300	10	8.2	31.7	804	10.7	272	36.4	16.5	OWL
255/55R18	109V XL	520 A B	B543	8.0	7.0 - 9.0	2271	1030	50	340	10	8.2	29.0	737	10.4	265	31.7	14.4	BSW
235/60R18	107V XL	520 A B	B540	7.0	6.5 - 8.5	2149	975	50	340	10	8.2	29.1	739	9.4	240	29.5	13.4	BSW
P245/60R18	104H	520 A B	B442	7.0	7.5 - 8.5	1984	900	44	300	10	8.2	29.6	751	9.7	248	30.2	13.7	BSW
P265/60R18	109T	520 A B	B463	8.0	7.5 - 9.5	2271	1030	44	300	10	8.2	30.5	775	10.7	272	33.0	15.0	OWL
P235/65R18	104T	520 A B	B435	7.0	6.5 - 8.5	1984	900	44	300	10	8.2	30.0	763	9.4	240	30.7	13.9	OWL
P265/65R18	112S	520 A B	B548	8.0	7.5 - 9.5	2469	1120	44	300	10	8.2	31.5	801	10.7	272	35.4	16.1	OWL
P275/65R18	114T	520 A B	B541	8.0	7.5 - 9.5	2601	1180	44	300	10	8.2	32.1	815	11.0	279	36.1	16.4	BSW
P255/70R18	112T	520 A B	B441	7.5	6.5 - 8.5	2469	1120	44	300	10	8.2	32.1	815	10.2	260	34.1	15.5	BSW
P265/70R18	114S	520 A B	B545	8.0	7.0 - 9.0	2601	1180	44	300	10	8.2	32.6	829	10.7	272	37.1	16.8	OWL
P245/55R19	103S	520 A B	B542	7.5	7.0 - 8.5	1929	875	44	300	10	8.2	29.7	753	10.0	253	31.1	14.1	BSW
275/45R20	110V XL	520 A B	B550	9.0	8.5 - 10.5	2337	1060	50	340	10	8.2	29.8	756	10.8	273	34.7	15.8	BSW
255/50R20	105H	520 A B	B621	8.0	7.0 - 9.0	2039	925	44	300	10	8.2	30.1	764	10.4	265	33.2	15.1	BSW
P275/55R20	111H	520 A B	B539	8.5	7.5 - 9.5	2403	1090	44	300	10	8.2	31.9	810	11.2	284	36.7	16.6	BSW
P275/60R20	114S	520 A B	B432	8.0	7.5 - 9.5	2601	1180	44	300	10	8.2	33.0	838	11.0	279	39.7	18.0	OWL

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim	Rim Width Range	Max. Load (s/d)		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 <sup>nd</sup>	mm	inch	mm	inch	mm	lbs	kg	
30X9.50R15LT	104R	C / 6	B458	7.5	6.5 - 8.5	1985	900	50	350	13	10.2	29.5	750	9.4	240	34.1	15.5	OWL
31X10.50R15LT	109R	C / 6	B446	8.5	7.5 - 9.0	2270	1030	50	350	13	10.2	30.5	775	10.6	268	37.9	17.2	OWL
LT235/75R15	104/101R	C / 6	B453	6.5	6.0 - 7.0	1985/1820	900/825	50	350	13	10.2	28.9	733	9.3	235	33.4	15.1	OWL
LT225/75R16	115/112R	E / 10	B457	6.0	6.0 - 7.0	2680/2470	1215/1120	80	550	13	10.2	29.3	744	8.8	223	35.6	16.1	BSW
LT245/75R16	120/116S	E / 10	B456	7.0	6.5 - 8.0	3042/2778	1380/1260	80	550	13	10.2	30.5	774	9.8	248	41.4	18.8	OWL
LT265/75R16	123/120R	E / 10	B434	7.5	7.0 - 8.0	3415/3085	1550/1400	80	550	13	10.2	31.7	804	10.5	267	46.0	20.9	OWL
LT215/85R16	115/112R	E / 10	B544	6.0	5.5 - 7.0	2680/2470	1215/1120	80	550	13	10.2	30.4	772	8.5	216	35.5	16.1	BSW
LT235/85R16	120/116R	E / 10	B450	6.5	6.0 - 7.5	3042/2778	1380/1260	80	550	13	10.2	31.7	806	9.3	235	40.9	18.6	BSW
LT245/70R17	119/116R	E / 10	B439	7.0	6.5 - 8.0	3000/2755	1360/1250	80	550	13	10.2	30.6	776	9.8	248	39.5	17.9	BSW
LT265/70R17	121/118S	E / 10	B431	8.0	7.0 - 8.5	3195/2910	1450/1320	80	550	13	10.2	31.7	804	10.7	272	45.4	20.6	OWL
LT245/75R17	121/118S	E / 10	B547	7.0	6.5 - 7.5	3195/2910	1450/1320	80	550	13	10.2	31.5	800	9.8	248	42.6	19.3	BSW
LT235/80R17	120/117R	E / 10	B546	6.5	6.0 - 7.5	3085/2835	1400/1285	80	550	13	10.2	31.8	808	9.3	235	40.8	18.5	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall  
 OWL Outline White Letter

